



# Raptor+

GLUNZ & JENSEN 




work positive



▲ Easy to operate graphic touch screen with logical menu. Optional native language plug-in and built-in remote support and diagnostics.

▼ Replenishment is precisely calculated based on processed square meters and time, maintaining stable, waste-free processing.



All electrical and mechanical components are located on the sides of the processor, for easy and convenient access during maintenance.



▲ Rollers and brushes are mounted with snap lock bearings, so they can be instantly replaced without tools or the need to re-calibrate pressure.

▼ Maintenance-free worm gears drive the rollers and provide smooth and trouble-free plate transport inside the processor.

Easy-lift top covers provide good access to the inside of the processor.

The electronics are conveniently located on the side of the processor.



The filter is conveniently mounted under the frame, giving easy access. Extra space under the processor can be used to place chemistry containers



Raptor+ T	
<b>MODEL</b>	85
<b>PERFORMANCE</b>	
Market position	Medium capacity
Plate types	Thermal plates
Plate width (max)	850mm (33.5")
Plate length (min)	274mm (10.8")
Plate thickness	0.15-0.3mm (0.006-0.012")
Processing speed	40-140cm/min (15.7-55.1"/min)
<b>CONSUMPTION</b>	
Tank capacity (developer)	22 l (5.8 US gal)
Temperature range (pre-heat)	N/A
Temperature range (developer)	20-40 °C (68-104 °F)
Water (draining)	16 l/min (4.2 US gal/min)
Water (recirculating)	0.2 l/m <sup>2</sup> (0.8 US gal/m <sup>2</sup> )
Power (stand-by)	0.06kW (200BTU/hour)
Power (operate)	1.8kW (6,000BTU/hour)
<b>GENERAL</b>	
Dimensions (LxWxH)	115 x 126 x 101-110cm (45.3 x 49.4 x 39.8-43.3")
Weight	235kg (518lbs)
Approvals	UL, c-UL certified. Complies with CE standards and RoHS directive.
Standard	Configured for typical applications in developer, Automatic container level alarm, Universal front panel, World-wide electrical configurable, Graphical finger touch control panel, Cooling unit, standard capacity 50/60 Hz, Hand shower for easy cleaning, WEBCONNECT
Accessories	Closed stand, Drip tray, Delivery table (L = 710 mm), Feed table (L=400 mm), Dedicated application configuration kits, Online interfaces for CtP, Remote Enabling System, Water saving, USB Memory stick, Stackers

## COMPACT. RELIABLE. EASY TO USE.

The Raptor+ processor is the ideal processing solution for any medium segment printers.

The Raptor+ processor offers many of the same features and benefits as the InterPlater HDX in a smaller footprint, targeting customers in the medium segment. This means that Raptor+ offers a high level of configuration flexibility and can be adapted to a wide range of applications, to better match the individual needs of the printer.



### Raptor+ Thermal

For traditional thermal plates with developer, wash, gum and dryer steps.



Note: Specifications are subject to changes without prior notice.

Learn more about Raptor+  
by scanning this QR code.



**Glunz & Jensen (Headquarters)**  
Selandia Park 1  
4100 Ringsted, Denmark  
+45 5768 8181  
gj@glunz-jensen.com

**Glunz & Jensen (Ringe)**  
Nordmarken 2  
5750 Ringe, Denmark  
+45 6262 4165  
gj@glunz-jensen.com

**Glunz & Jensen (Milan)**  
Via Alessandro Volta 28  
20088 Rosate (MI), Italy  
+39 02 900 90 180  
gj@glunz-jensen.com

**Glunz & Jensen (Americas)**  
500 Commerce Drive  
Quakertown, PA 18951, USA  
+1 267 405 4000  
gj-america@glunz-jensen.com

**Glunz & Jensen (Asia)**  
Suzhou, 215129  
P.R. China  
+ 86 136 1291 5142  
gj@glunz-jensen.com

**Glunz & Jensen Thetford**  
Unit 4-6, Napier Place  
Stephenson Way Industrial Estate  
Thetford, Norfolk, IP24 3RL, UK  
+44 1842 765128  
gj@glunz-jensen.com



Preventive Maintenance Kits  
are available for this product  
to maximize production uptime.

**GLUNZ & JENSEN** 

[www.glunz-jensen.com](http://www.glunz-jensen.com)